


ER057005NC6 / 5.7" CSTN LCM

PIN ASSIGNMENT



GENERAL INFORMATION

LCD Type	5.7" Color STN Display
Resolution	320 (RGB) * 240 Dots
Display Color	65K color
Module dimesions	167 (W) * 109 (H) * 8.9 (T) mm
Viewing Area	118.18 (W) * 89.38(H) mm
Active Area	115.17(W) * 86.37(H) mm
Viewing Angle	Y: +30 -60, X: +58 deg.
Dot Pitch	0.12 (W) * 0.36 (H)
Polarizer Type	Transmissive
Luminance	150 cd/m Typ (Min)
Contrast Ratio	50
Backlight	CCFL
Interface	BY CONTROLLER

PIN NO	SYMBOL	LEVEL	FUNCTION			
1	FLM	H	SYNCHRONOUS SIGNAL FOR DRIVING SCANNING LINE			
2	CL1	H → L	DATA SIGNAL LATCH CLOCK (LOAD)			
3	CL2	H → L	DATA SIGNAL SHIFT CLOCK (CP)			
4	DISOFF	H/L	DISPLAY CONTROL SIGNAL , H:DISPLAY ON L:DISPLAY OFF			
5	VDD	-	H	H	H	6800-SERIES 16 BIT INTERFACE
6	VSS	-	L	L	X	3 PIN SPI (WRITE ONLY)
7	VLCD	-	L	H	X	4 PIN SPI (WRITE ONLY)
8	D7	H/L	DISPLAY DATA			
9	D6					
10	D5					
11	D4					
12	D3					
13	D2					
14	D1					
15	D0					
16	VSS	P	GROUNG			

CCFL INTERFACE

PIN NO	SIGNAL	LEVEL	FUNCTION
1	HV	AC	POWER SUPPLY FOR CCFL (HOT)
2~3	NC	-	NO CONNECTION
4	GND	-	POWER SUPPLY FOR CCFL (GND)

DIMENSIONS

UNIT : mm
 SCALE : NTS
 NOT SPECIFIED TOLERANCE IS ± 0.5

